

Ref. ZP-TC-27-010123-01

Technical Data Sheet

<p>Main application Cleaning of all type of Ceramic, Glazed, Vitrified & Glass mosaic tiles. Removes complete dirt and maximum stain from the tiles surface and provide superior shine.</p>	<p>Zeoclean Power Tile Cleaner is an ideal powerful tile cleaner for daily and often use. It is based on high quality formulation to clean the surface of tiles, sandstone or concrete to remove the dirt, soil, salt deposits, mud, different stain & other particle completely. Suitable for internal & external areas on floor and on wall.</p>
--	--

Technical advantage of Zeoclean Tile Cleaner over traditional cleaner

- Guaranteed cleaning of all dust, dirt, stain and residual from tiles surface.
- Easy to use in pure form or can be diluted with clean water.
- Best to use for daily maintenance on floor and wall with dilution of water.
- Fast reaction with surface within 1 to 5 minutes. Based on thickness of dirt or stain.
- Effective in removing cement & cement-based grout stain.
- Safe to hand and skin for temporary contact.

Suitable areas

- Internal & external wall & floor.
- Residential & commercial buildings.
- Industrial facilities.
- Commercial kitchens.
- Under construction job site.
- Before grouting the tiles.

Suitable surfaces


- Ceramic, Glazed & Quarry Tiles. (Unglazed Tiles, please test small area first.)
- Porcelain & Vitrified tiles.
- Glass mosaic & Glass tiles.
- Stained brick, Kota Stone & Terracotta surfaces with efflorescence. (Dilute the cleaner with clean water as per need.)
- Cement based surface such as plaster & concrete. (Dilute the cleaner as per need.)

Product not to be used

- On polished Granite & Marble. (Use Zeoclean Marmo – Marble & Stone cleaner).
- Tiles surfaces which are unglazed and delicate to strong solutions. Test small area first with dilution of water.
- On Sanitary & Chrome finished sanitary Tap. (Use Zeoclean Dayna - Sanitary & Tape Cleaner.)
- On steel & polished metal surfaces where surface shine may get affected.
- On wood surface.
- To remove Epoxy Grout haze / film from tile surface. (Use Zeoclean Max - Epoxy Film Remover.)

Technical Data Sheet

How to Use



Important tools for application:

- Hand Gloves, Sponge or cloth for spreading the solutions on surface.
- Scrubber pad or similar tools for rubbing the dirty surface.
- Other cleaning tools such as bucket, wiping cloth. Scrub machine for old floor etc.

Cleaning of tools:

- All the tools which are used for application can be clean with normal water and can be left for dry.

Surface Preparation

- The area which is to be cleaned ensure that no other material or surface are exposed which are delicate (Wood, metal or carpet etc.) to strong solutions. The delicate expose surface can be covered with plastic protection sheet or any other material.
- Any loose or excess dry dirt can be removed first from the floor in order to have fast reaction of product with stain / dirt directly which helps in cleaning faster.

Technical Data Sheet

Mixing:

- Shake the bottle / container well before using.
- Zeoclean Power Tile Cleaner can be used pure for heavy stained surfaces such as construction job site or old unused area.
- For mild stained, the cleaner can be diluted from 1:1 till 1:10 or more with normal water. The dilution is fully depending on final results needed and cleaning technique.

How to apply:

- Spread the solutions on dirty surface directly. The waiting period can be 3 to 5 minutes depends upon how strong the stain is bonded to the tile surface.
- Repeat the application if stained have not been removed completely in first cleaning.
- Final clean the surface with enough normal water to remove the traces of cleaner.
- **PLEASE NOTE IN CASE CLEANER IS FULLY DRIED ON SURFACE AND NOT CLEANED WITH WATER, IT CAN CAUSE DAMAGE TO SURFACE.**

Product & Working Data

Product appearance	: Lite coloured liquid.
Packing	: 1 Kg. bottle & 5 Kg. can.
Shelf life	: Can be used until fully sealed. Once open use within a month for best results.
Dilution with Water	: Depends on dirt and stain deposited on surface.
How much to apply	: For hard stained surface, it should be fully saturated with cleaner. : For lighter stained surface, cleaner can be applied with sponge or cloth.
Waiting time before cleaning	: 3 to 5 minutes. For daily use mopping with moist cloth is sufficient.
Use of the cleaned surface	: Immediately once it is dry.
Coverage	: Depends on surface area and application technique.

Important instructions & precautions

- Keep away from eye / nose and don't inhale.
- Use safety gloves for prolong contact of cleaner with skin.
- Keep the lid tightly closed of bottle / container for unused / partially used product.
- In case of skin irritation or strong reaction, consult local doctor.
- Let cleaner don't stay on tile or other surfaces for longer than 5 to 10 minute and it should not dry.
- In case the performance of Walnut products not as per technical data mentioned, please call Walnut technical helpline.

Walnut Green Building Index

Walnut range of products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, Walnut procure the major raw material locally to safeguard environment.

Data Technical Sheet

Walnut Quality & Safety Assurance

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.



Declaration

All the above information and results are provided based on Walnut internal quality test. Customer must check before using the product about performance and final expected results. Walnut cannot be held responsible for any damage of whatsoever nature at site.

Technical Help

Walnut Building Solutions India Private Limited | CIN : U36999MH2017PTC289638

IJMIMA, 804, 8th floor, Behind Goregaon sports club, off link road, Malad West, Mumbai - 400064

Technical services & customer care: +91-22-49713322 / +91 9967007783 | email: info@wallnut.co.in