

Technical Data Sheet

Ref.: C-St.P.23-011123-03

<p>In Compliance With EN & IS norms</p>	<p>Calcibond Smart Plus is an Eco friendly, light weight, high polymer modified, mineral based, ready to use adhesive formulated with high quality raw material for fixing vitrified tiles in interior all areas and on external floor. Natural marble on internal floor and all type of ceramic, glazed tiles and ceramic mosaic in all internal & external all areas.</p>
<p>Main application Adhesive for fixing vitrified tiles in interior and on external floor. Natural marble on interior floor.</p>	



Technical advantage of Calcibond Smart Plus over cement or normal adhesive

- Conformity to Class 2 adhesive as per European Norms (EN) and Type 2 adhesive as per Indian Standard (IS) 15477: 2019
- Highly thixotropic (non-seg) for fixing vitrified & ceramic tiles on wall in all interior area.
- High Polymer modified and made with high grip technology.
- Guaranteed fixing of vitrified tiles in interior all areas and on external floor. Natural marble on internal floors.
- Exceed strength of Class 2 adhesive as per EN and Type 2 as per IS norms.
- High coverage and high workability among Type 2 adhesive available across industry.
- Suitable for renovation and tiles over tile work.
- No water curing required.
- Saving of time & labor.
- No need to mix any extra cement.
- No need to soak absorbent tiles into water prior to fixing.
- Very low VOC and suitable for green building.

Suitable areas

- Internal areas for Ceramic & Vitrified tiles. Internal floor for Indian Marble.
- Residential, commercial & industrial buildings.

Suitable surfaces

- Fully dry and sound new or old traditional plaster.
- New or old absorbent IPS or PCC floors which are sound and stable.
- Absorbent concrete.
- Screed made with Zeorich Base, Zeorich Base Rapid or similar type.

Suitable covering material

- All type & size of absorbent ceramic & porcelain tiles.
- Vitrified tiles of all type and Indian natural marble on flooring.
- Ceramic mosaic.

Product not to be used

- On non-absorbent or dense concrete surfaces (Use Calcibond Secure adhesive).
- On metal, wood, rubber & on cement board, use Calcibond Ultima.
- To fix stone of all type which are sensitive to moisture, use Calcibond Ultima.
- Italian marble or similar stone which are soft and brittle in nature, use Calcibond Advance or Calcibond Ultima.
- To fix recomposed stone or re-engineered marble, use Calcibond Advance or Calcibond Ultima.
- Over expansion joint or in area with extreme movement in structure.
- More than 12 mm. and less than 3 mm. of thickness.



How to Use

Important tools for application:

- Electric low speed mixing stirrer.
- Walnut notch trowel of 6x6 mm. size & 10x10 mm.
- Auto spirit level
- Other mixing & finishing tools such as mixing trowel, bucket, brush, broom, measuring tape etc.

Cleaning of tools:

- While still the material is fresh, all the tools can be cleaned with normal water. Once material is hardened, the material can be removed only by mechanical means.

Surface Preparation

- Ensure that plaster / screed surface is sound, clean and free from all foreign material such as oil, grease, dust etc.
- If surface is uneven of more than 10 mm. than first do the levelling by using correct levelling material in order to avoid using excess thickness of adhesive or apply first thin coat of same adhesive to level the surface and wait for 24 hours.
- Onto dry clean surface, splash the enough water and let it surface dry to improve the workability of adhesive.
- In case working in external environment, avoid direct sun exposure to surface and to finishing material. Let cool the surface before starting application. Hot surface may compromise final performance.
- If surface area is larger, provide movement joint every 3 meters.
- Follow concrete expansion joint and connection joint as per standard.

Mixing:

- Mix Calcibond Smart Plus 20 kg. grey or white bag with approx. 4.5 to 5 lt. of clean water. Use slow speed electric stirrer to have desire results. Manual mixing can compromise performance of adhesive.
- Adjust the water quantity as per ambient temperature and dryness of surface. The final mix must be workable paste.

How to apply:

- Spread the adhesive in desire thickness from 3 to 12 mm. onto cement surface using proper notch trowel.
- Once adhesive is applied, fix the tiles or stone onto adhesive before skin formation and press firmly. In case tiles or stone are of big size, also apply the adhesive layer at the back of tiles.
- Leave the space between tiles to have proper grouting and to accommodate surface movement.
- Leave the tiles for 24 hours to bond well and then follow the grouting process.

Product & Working Data

Product appearance	: Grey and white colour powder
Packing	: 20 & 40 Kg. moisture proof bag
Shelf life	: 12 months from the date of manufacturing.
Water ratio	: Approx. 4.5 to 5 lt. for grey and white per 20 kg. bag
Pot life	: > 2 hours
Thickness limit	: Minimum 3 to maximum 12 mm.
Open Time	: ≥ 30 minute
Adjustability	: > 30 minute
Initial setting	: 6 to 8 hours.
Final setting	: 24 hours.
Walking on floor	: After 24 hours.
Grouting	: After 24 hours.
Normal use of surface	: After 2 weeks.
Full strength of adhesive	: At 28 days.
Coverage	: Approx. 60 sq. ft. / bag of 20 kg. Using 3 mm. thick or 1.2 kg. / m ² / mm.
Application temperature	: + 5° C. to + 35° C.

(Data @ 23°C. & 50% humidity)

Technical Performances

In compliance with (Indian Standard) IS 15477-2019: for Type 2 Tile Adhesive

Tensile Adhesion (Dry condition) : ≥ 1.1 to 1.25 N/mm²

Sheer Adhesion

Dry Condition : ≥ 1.25 N/mm²

Heat Ageing Condition : ≥ 1 N/mm²

Wet Condition : ≥ 1 N/mm²

(Final results @ 28 days. 27° C. & 65% humidity)

- Final resistance to temperature after 28 days or full cure: - 30 to + 70° C.
- The final results at test site may vary based on temperature and humidity & surface condition.

Technical Performances

In compliance with (European Norms) EN 1348 – Class C2 Tile Adhesive test requirement:

Initial adhesion (After 28 days) : ≥ 1 N / mm² }

Adhesion after heat cycle : ≥ 1 N / mm² }

Adhesion after water immersion : ≥ 1 N / mm² }


Adhesion after freeze / thaw cycle : ≥ 1 N / mm² }

Exceed all results than EN Norms.

(Final results @ 28 days. 23° C. & 50% humidity)

- Final resistance to temperature after 28 days or full cure: - 30 to + 70° C.
- The final results at test site may vary based on temperature and humidity & surface condition.

Walnut Exclusive Technology



Important instructions

- Once bags are open, entire material must be consumed within 24 hours. Store the bags in safe environment.
- In case of very weak cement surface, please ensure that proper strength or correction are done before use of adhesive.
- If temperature is more than 35° C., than avoid using the products under direct sun.
- In case temperature is cold and below 5° C., the initial and final setting may affect.
- Expansion & connection joint must be followed of concrete and all other elements of concrete structure.
- For any structure related issue, follow local code and appropriate consultant guidelines.
- In case the performance of Walnut products not as per technical data mentioned, please call Walnut technical helpline.

Walnut Range of Tile Adhesives and Recommended Application

Fixing Material									
Walnut® Tile & Stone Adhesives	AAC Block / Fly Ash bricks	Ceramic / Clay & Glazed tiles	Vitrified Tiles upto 2x2'	Vitrified Tiles Slab	Ceramic Mosaic	Glass Mosaic	Marble & Granite tiles	Marble Granite Slab	Enginnered Quartz Stone
Lite Tile	X	✓	X	X	X	X	X	X	X
Lite Tile Plus	X	✓	✓	X	X	X	X	X	X
Lite Block	✓	✓	X	X	X	X	X	X	X
Lite Floor	X	✓	✓	✓	X	X	✓	✓	X
Calcibond Smart	✓	✓	✓	✓	✓	X	✓	✓**	X
Calcibond Smart Plus	✓	✓	✓	✓	✓	X	✓	✓**	X
Calcibond Secure	✓	✓	✓	✓	✓	✓	✓	✓**	X
Calcibond Flex	✓	✓	✓	✓	✓	✓	✓	✓**	X
Calcibond Advance	✓	✓	✓	✓	✓	✓	✓	✓	✓**
Calcibond Ultima	✓	✓	✓	✓	✓	✓	✓	✓	✓

Strike with star (**) mark it is recommended to use Walnut Calcibond Latex as replacement of water in part or full for best results. For further detail and if any fixing material not covered above or doubt, please consult Walnut Technical Department before using the product.

Application Surfaces									
Walnut® Tile & Stone Adhesives	Plaster	Cement Screed / PCC	Traditional Concrete	Mivan / Precast Concrete	Existing Tiles	Wood	Metal	Dry Wall	Rubber floor
Lite Tile	✓	✓	X	X	X	X	X	X	X
Lite Tile Plus	✓	✓	X	X	X	X	X	X	X
Lite Block	✓	✓	X	X	X	X	X	X	X
Lite Floor	✓	✓	X	X	X	X	X	X	X
Calcibond Smart	✓	✓	✓	✓**	✓**	X	X	X	X
Calcibond Smart Plus	✓	✓	✓	✓	✓	X	X	X	X
Calcibond Secure	✓	✓	✓	✓	✓	X	X	X	X
Calcibond Flex	✓	✓	✓	✓	✓	X	X	X	X
Calcibond Advance	✓	✓	✓	✓	✓	X	X	X	X
Calcibond Ultima	✓	✓	✓	✓	✓	✓	✓	✓	✓

Strike with star (**) mark it is recommended to use Calcibond Latex as replacement of water in part or full for best results. For further detail and if any surface area is not covered above, please consult Walnut Technical Department before using the product.

Application Areas									
Walnut® Tile & Stone Adhesives	Internal Floor	Internal Wall	External floor	External Wall upto 10 feet	External Building Façade	Lift area / Lobby	Roof / Terrece	Balcony	Swimming Pool
Lite Tile	✓	✓	X	X	X	X	X	X	X
Lite Tile Plus	✓	✓	X	X	X	X	X	X	X
Lite Block	X	✓	X	✓	X	X	X	X	X
Lite Floor	✓	X	✓	X	X	X	X	X	X
Calcibond Smart	✓	✓	✓	✓	✓**	✓**	X	✓	X
Calcibond Smart Plus	✓	✓	✓	✓	✓**	✓**	X	✓	X
Calcibond Secure	✓	✓	✓	✓	✓**	✓**	✓	✓	✓
Calcibond Flex	✓	✓	✓	✓	✓**	✓	✓	✓	✓
Calcibond Advance	✓	✓	✓	✓	✓	✓	✓	✓	✓
Calcibond Ultima	✓	✓	✓	✓	✓	✓	✓	✓	✓

Strike with star (**) mark it is recommended to use Calcibond Latex as replacement of water in part or full for best results. For further detail and if any application area is not covered above, please consult Walnut Technical department before using the product.

Technical Data Sheet

Walnut Green Building Index

- Walnut range of products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, Walnut procure the major raw material locally to safeguard environment.



- Recycled raw material used.
- VOC-Very low organic compounds.
- 100% suitable to recycle after expiry.
- Suitable for all kind of green/normal buildings.

Walnut Quality and Safety Assurance

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.



Declaration

All the above information and results are provided based on Walnut internal quality test. Customer must check before using the product about performance and final expected results. Walnut cannot be held responsible for any damage of whatsoever nature at site.

Technical Help

Walnut Building Solutions India Private Limited | CIN : U36999MH2017PTC289638

IJMIMA, 804, 8th floor, Behind Goregaon sports club, off link road, Malad West, Mumbai – 400064

Technical services & customer care: +91-22-49713322 / +91 9967007783 | email: info@walnut.co.in